

DL5.0

DL5.0 has a larger capacity design for residential and commercial storage applications. Up to 50 batteries can be connected in parallel to meet the needs of more users. The optional OTA function enables remote update & easy monitoring. Powerful, high capacity and modular.



APP Monitoring (optional)
Real-time monitoring
& Remote upgrade available



Module Design
Flexible expansion



Easy Installation
Stackable with
flexible brackets



High Safety LFP
Cell level monitoring and balancing



Wide Compatibility
Matching with leading inverters

Technical Specifications

Model	DL5.0
Battery Type	LiFePO4
Nominal Battery Energy / Usable Energy	5.12 kWh/4.61kWh
Nominal Capacity	100Ah
Nominal Voltage	51.2V
Operating Voltage	44.8 ~ 57.6V
Recomended Charge & Discharge C Rate	0.5C
Recommended Charge/Discharge Current	50A
Max. Power Charge /Discharge Current	90A/98A
Max. Charge /Discharge Power	4.61kW/5.02kW
Depth of Discharge (DOD)	90%
Net Weight	44kg
Dimension[W*D*H]	481*535*140 mm
Charging Temp. Range	0~45°C
Discharging Temp. Range	-20~55°C
Communication	CAN/RS485/RS232
Cycle Life ^[1]	≥6000 Cycles
Protection Level	IP20
Expansion	Up to 50 units in parallel
Pros	Can be used in both off-grid and hybrid setups, compact design
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619
Compatible Inverters	SMA/Victron/Ingeteam/Delios/Goodwe/Solis /Deye/SAJ/Voltronic/Sungrow etc.

[1]Test conditions: 0.2C Charging/Discharging, @25°C, 90% DOD

Manufacture: Daqin New Energy Tech(Taizhou) Co., Ltd.

Made in China.

Address:No.511 West Chenzhuang Road, Sanshui Street, Jiangyan District, 225500Taizhou City, Jiangsu Province, China,